

MTN

Horizons® CT Soft Touch Filtration Cooler



Horizons® CT Soft Touch



Features

- 1.4L / 0.37G Stainless steel hot tank
- 3.55L / 0.94G stainless steel cold tank
- 17.5" tall - fits under most cabinets
- Touch sensitive activation panel - no moving parts
- Large 10" dispensing area to accommodate a variety of container sizes
- Lighted spout and dispensing area
- Filtration system can be setup to run outside of cooler
- Dual mechanical float
- Hot water safety lock
- Fast flow water dispensing
- Removable, dishwasher safe drip tray
- Available in black - custom color and logo options available
- UL listed
- **Accu-Temp™** - Serves water at the proper temperature every time



Power

Voltage	115V
Frequency (Hz)	60
Power Consumption	517W
Cold Power Consumption	67W
Hot Power Consumption	450W
ES (kWh/24 hrs.)	0.646
% lower than ES Standard	26%

Hot Water System

Avg. Hot Water Temp at Nozzle @ 77°F Ambient (Cut-in / Cut-out Temp)	174°F / 190°F
Hot Water ARI Rating	31, 6 oz. > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +/- 5.5°F
Hot Thermostat / Thermistor Cycle	172°F / 190°F
Hot Water Flow Rate	1.06 - 1.17 oz./sec
Hot Tank Size (L)	1.4L
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F Ambient (Cut-in / Cut-out Temp)	45.7°F / 41.2°F
Cold Water ARI Rating	34, 5 oz. < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°F/-8°F
Cold Water Flow Rate	1.06 - 1.17 oz./sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.56 / 2.65 / 1.32 : 0.94 / 0.7 / 0.35

Weights and Measurements

Net Weight (Lbs.)	28
Gross Weight (Lbs.)	30.9
Max Distance from Drip Tray to Faucet (Inch : mm)	10.25 : 260.35
Faucet / Dispense Height (Inch : mm)	28.75 : 730.25
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.8x17.9x17.5 / 13.4x17.7x18.5
Container Load (20')	340
Container Load (40')	700
Container Load (40' HC)	875
Container Load (45' HC)	979
Certifications	UL Listed
Models (H&C)	HCB 215ST

Warranty:

3 years: Sealed refrigeration system

2 years: Parts (electrical to include cold controls, relay overloads and PCB's)

phone: (909) 629-7301)**Canada:** (905) 302-7896**email:** info@aquabeve.com**web:** www.aquabeve.com